






Ventilation / Display Performance Considerations

- 1) Area in which display is to be sited must have a minimum room floor area no less than 22 sq m.
- 2) Install over a sealed floor or ventilated floor void.
- 3) Do not site the display within 2m of ceiling mounted air conditioning grilles.
- 4) Do not site the display beneath a high level of direct sunlight.
- 5) Display will operate in a 24 hour environment.



OPTIONAL FRONT FASCIA PANELS
GDKSF15 - SATIN STAINLESS STEEL
GDKBF15 - BLACK PLASTISOL
FOR FREE STANDING MODELS




APPROX. UN-CRATED
WEIGHT OF UNIT: 200Kg



CED FABRICATIONS LTD
UNITS A1-A4, FALCON COURT
CLAYTON BUSINESS PARK
CLAYTON-LE-MOORS
HYNDBURN
LANCASHIRE BB5 5JD

This drawing and information herein is confidential to CED Fabrications Ltd. It is issued in confidence that it will not be disclosed to any third party in part or in whole without permission from CED FABRICATIONS Ltd.

© CED FABRICATIONS LTD



DESCRIPTION:

GLASS DISPLAY KING ROLL-IN
1500mm CHILLED DISPLAY
HYDROCARBON TYPE-R290 REFRIGERANT

SCALE: 1 : 2.5 @ A4 REV No: C

PRODUCT
CODE:

GDK1500