



Wall Sited Soup Station (Self Help)



Wall Sited Soup Station (Rear Side)

Wall Sited Soup Station (Customer Side)

ABOUT

The wall sited soup station dry heat bain marie & ambient storage cupboard form part of the Glide range of mobile dining carts - a choice of cold, hot & ambient commercial catering carts that combine to form a food service counter solution as unique as your requirements !

The wall sited soup station fits neatly against walls, in an alcove, recess or back to back when used as island units. It has a bain marie insert within a s/steel worktop and is available as 2-1Gn size, 825mm(l) 700mm(d) x 900mm(h). The self help bain marie soup section features a removable drip tray to the front with 2 no. 4.5 lt. soup pots to the rear. Notched container lids (for ladles) are also included. The soup containers are heated from a suspended hairpin heating element underneath.

The ambient storage cupboard below has 2 tier adjustable internal grid shelves, both are removable for cleaning. The front facing sliding cupboard doors are also removable for access. The rear/side base panels & cupbd. doors are in leathergrain plastisol steel, colour merlin grey (BS 18B25). The unit has lockable castors and control panel to customer side. It is supplied with a 3m lead and a 13A UK plug top (0.75 Kw).

The soup station features thermostatic control & a neon mains power on/off switch.

HEIGHT OPTIONS

Low Height Model (Glide Junior).
850mm or 800mm high options for junior/ primary use.



Download All Technical Drawings From www.cedfabsltd.co.uk

FEATURES

Model Type.

The Glide wall sited soup station is a mobile dry heat bain marie & ambient storage cupboard with full rear/ side fascia panels, a s/steel bain marie insert & ambient cupboard with two tiers of wire rack shelving below. Each shelf is adjustable in height and fully removable for cleaning. The front facing sliding doors are also removable. The wall sited soup station features 2 x 4.5 litre containers with notched lids (for ladles) and a removable drip tray section to the front, for self help use. The containers can be used to hold gravy, custard etc. by adjusting the thermostat control.

Model Dimensions.

The Soup Station is available as 2-1Gn (825mm) long x 700mm (D), 900mm (H) & has locking heavy duty castors.

Model Finishes.

Rear base, outer end panels and sliding doors are finished in plastisol steel, colour merlin grey. The bain marie worktop is made from 304 gd s/steel & the remaining steel surfaces are in 430gd.s/steel.

Low Maintenance.

Easy, cleanable surfaces and a durable design ensure low maintenance for users.

Finishes & Options.

The wall sited soup station can be customised with many accessories such as tray slides, tray rails, colour finishes and low height versions for junior/ primary age use.

Power Supply.

The cupboard is fitted with a 3m lead & 13 amp UK plug (13A 230v 50Hz). The unit has a 0.75kW electrical supply.

Equipment Conformity.

CE & UKCA Certified equipment.

Temperature Controls.

The Soup Station bain marie features a thermostat control. Mains power is operated by individual neon indicator switch.

ACCESSORIES & FINISHES

Folding Steel Solid or Tubular Tray Slides.

Drop down tray rails or slides + 40mm (d) height = (h) - 55mm.

Selection Of Colour Finishes To Base & Doors.

11 alternative choices of durable steel, colour & wood effect for the external rear/ side base panels.& sliding cupboard doors.



2 x 4.5 litre containers with notched lids



Glide Wall Sited Soup Station (Bain Marie)

Code	Description	Capacity (Gn)	Dimensions (L x D x H mm)	Depth With Tray Slide Up/ Down	Weight (kg)	Total Power (kW)
GWSSUP2	Glide WS Soup Str./ Amb..Cupbd	2-1	825 x 700 x 900	1000/ 740mm	45	0.75

Model Description. (GWSSUP2) Glide mobile dining cart, (wall sited) soup station c/w bain marie insert within s/steel worktop. Electric, 2-1Gn, 825(l) x 700(d) x 900(h). Self help use, 1x removable drip tray to front, 2x 4.5 lt. soup pots to rear. Containers c/w notched lids (for ladles), can be used to hold gravy, custard etc. by adjusting thermostat control. Ambient storage cupboard under with 2 tier adjustable internal grid shelves, removable for cleaning. Removable front facing (customer side) sliding cupboard doors. Rear/side base panels & cupboard doors in leathergrain plastisol steel, colour merlin grey (BS 18B25), lockable castors, control panel to front (customer side), 3m lead, 13A UK plug top 0.75 Kw Bain marie soup station features thermostatic control & neon mains power on/off switch.(Tray Rail Optional)

For best performance always keep lids on containers when not serving, stir food in containers regularly

Glide S/Steel Folding Tubular Tray Rail

Code	Description	Capacity (Gn)	Dimensions (L x D x H mm)	Weight (kg)
GTTS2	Glide S/Steel Drop Down Tray Rail	2-1 Gn	825 x 298 x (base-55)	2

Wall Sited Soup Station (B.Marie)

Option Description.
S/steel tubular tray rail, 304 gd. Ø25 tube, drop down bracket type, up position depth + 298 mm to base unit, down position depth + 40mm to base unit. Trayslide height = base unit (h) - 55mm.

Glide S/Steel Folding Solid Tray Slide

Code	Description	Capacity (Gn)	Dimensions (L x D x H mm)	Weight (kg)
GSTS2	Glide S/Steel Drop Down Solid Tray Slide	2-1Gn	825 x 302 x (base-55)	3


Wall Sited Soup Station (B.Marie)

Option Description.
S/steel solid tray slide, drop down bracket type, up position depth + 302 mm to base unit, down position depth + 40mm to base unit. Trayslide height = base unit (h) - 55mm.



Wall Sited Soup Station

OPTIONS, FINISHES, & POPULAR MODEL CODES



Low Height Model (Glide Junior) - 800/ 850mm (h)

Code	Description	Base Height (mm)	Optional Tray Slide Height (mm)
G800H**	Glide Base Unit 800mm Height	800	745
G850H	Glide Base Unit 850mm Height	850	795

**G800H Bespoke Option (With Extended lead Time)

Wall Sited Soup Station (B.Marie)

Option Description.
Lower height option codes for junior/ primary use.
****800mm (h) base unit, c/w 100mm lockable castors. (Optional trayslide height becomes 745mm high)****
850mm (h) base unit, c/w 100mm lockable castors. (Optional trayslide height becomes 795mm high).

Colour Finishes To Base Cupboard (Front /Sides/Rear)

11 choices of leathergrain plastisol steel colours/ wood effect laminated steel for front opening sliding cupbd. doors/ sides.



Model GWSSUP2
Option GGRENWSA2 Shown



Model GWSSUP2
Option GBEECWSA2 Shown

Code	Description	Capacity
Ocean Blue (BS 18C37)		
GBLUEWSA2	Glide Blue Cupbd.Amb.(Wall)	2-1Gn
Goosewing Light Grey (BS 10A05)		
GGREYWSA2	Glide Grey Cupbd.Amb.(Wall)	2-1Gn
Poppy Red (BS 04E5B)		
GPREDWSA2	Glide Red Cupbd.Amb.(Wall)	2-1Gn
White (BS 00E55)		
GWHITWSA2	Glide White Cupbd.Amb.(Wall)	2-1Gn
Wood Grain Effect Panels DL85 Walnut Finish		
GWALNWSA2	Glide Walnut Cupbd.Amb.(Wall)	2-1Gn

Code	Description	Capacity
Satin S/Steel (430 gd.)		
GSSTLWSA2	Glide S/Steel Fascia - Ambient	2-1Gn
Forest Green/Heritage (RAL 6002)		
GGRENWSA2	Glide Green Cupbd.Amb.(Wall)	2-1Gn
Buttermilk Cream/ Honesty (BS 10C31)		
GCREMWSA2	Glide Cream Cupbd.Amb.(Wall)	2-1Gn
Black (BS 00E53)		
GBLAKWSA2	Glide Black Cupbd.Amb.(Wall)	2-1Gn
Wood Grain Effect Panels DL76 Beech Finish		
GBEECWSA2	Glide Beech Cupbd.Amb.(Wall)	2-1Gn

POPULAR MODEL CODES



Glide Wall Sited Soup Station (Self Help)

Model Code	Description	Total Power (kW)
GWSSUP2	Glide Wall Sited Soup Stn./ Amb. Cpbd 2-1Gn	0.75

*Requires 13A 230V Elec. Socket.

Glide Wall Sited Soup Station (& Tray Slide)

Model Code	Option Description	Total Power (kW)
GWSSUP2	GSTS2 Glide WS Soup Stn./ Cpbd.T.Slide 2-1Gn	0.75

*Requires 13A 230V Elec. Socket.



Glide Wall Sited Soup Station (& Tray Rail)

Model Code	Option Description	Total Power (kW)
GWSSUP2	GTTS2 Glide WS Soup Stn./Cpbd. & T.Rail 2-1Gn	0.75

*Requires 13A 230V Elec. Socket.

Glide Wall Sited Soup Station (& Tray Slide & Colour Finish - Red)

Model Code	Option Code	Option Code	Description	Total Power (kW)
GWSSUP2	GSTS2	GPREDWSA2	Glide WS Sp Stn/T.Slide+(Red) 2-1	0.75

*Requires 13A 230V Elec. Socket.



Glide Wall Sited Soup Station (& Colour Finish - Green)


Model Code	Option Code	Description	Total Power (kW)
GWSSUP2	GGRENWSA2	Glide WS Sp. Stn.+(Green) 2-1Gn	0.75

*Requires 13A 230V Elec. Socket.


Glide Wall Sited Soup Station (& Tray Rail & Colour Finish - Red)

Model Code	Option Code	Option Code	Description	Total Power (kW)
GWSSUP2	GTTS2	GPREDWSA2	Glide WS Sp Stn/T.Rail+(Red) 2-1	0.75


*Requires 13A 230V Elec. Socket.



Glide Wall Sited Soup Stn.



Glide Wall Sited Soup Stn./Tray Rail



Glide Wall Sited Soup Stn./Tray Slide

